

Thermowell Key Features

Table top food preparation well designed to ensure a flexible workflow planning



01. Removable condensing unit cover for easy servicing and maintenance
02. Hinged lid designed to stay open for easy access and the ease of cleaning
03. Fitted with digital thermometer for clear temperature display
04. Excellent thermal efficiency, high density polyurethane insulation with Zero ODP (Ozone Depletion Potential) and Low GWP (Global Warming Potential)
05. Fitted with rubber feet offering non-slip placement
06. Imported, durable and energy-efficient compressor
07. Accurate helium leak detection system ensures the quality of the entire refrigeration system
08. Designed and engineered to operate up to 32°C ambient
09. Environmental-friendly CFC-free refrigerant (R134a)
10. HACCP compliant

Thermowell

Specification

- Accommodates 1/3 GN size (100mm depth)
 - Foodsafe 304 grade stainless steel exterior (including back) and interior
 - Galvanised steel exterior base
 - Fitted with adjustable thermostat
-

Options

1. 304 grade stainless steel exterior base
2. Air-blown system *
3. Acrylic sliding cover
4. Glass hood in lieu of hinged lid
5. Wall / counter mounting kit
6. GN pan bridging bar
7. 220V / 60HZ / 1PH

* Dimension and capacity are different, please check with Williams

Product List

| TW9 | TW15 | TW18 |
|---|---|---|
|  |  |  |

Thermowell Technical Data

| Model | TW9 | TW15 | TW18 |
|--|-------------------|---------|---------|
| Temp Range (°C) | +4 / +8 | +4 / +8 | +4 / +8 |
| External Dimension (mm) | | | |
| Width | 980 | 1510 | 1862 |
| Depth | 375 | | |
| Height | 241 | | |
| Internal Dimension (mm) | | | |
| Width | 685 | 1212 | 1565 |
| Depth | 305 | | |
| Height | 105 | | |
| Thickness of 304 grade stainless steel (mm) | | | |
| Exterior | 0.7 | | |
| Interior | 0.6 | | |
| Lid | 0.9 | | |
| Opening Height (mm) | 575 | | |
| Capacity (1/3 GN pan) | 4 | 7 | 9 |
| Power Supply | 220V / 50HZ / 1PH | | |
| | 13 amp plug | | |
| Power Input - Running (amps) * | 1.25 | | |
| Rating Power (watts) * | 275 | | |
| Compressor (HP) | 1/6 | | |
| Heat Rejection (watts) (Evaporating at -10°C in 32°C ambient) | 204 | | |
| Refrigerant | R134a | | |

* 20% increase for 60HZ power supply