

# Aztra Key Features

Space saving design allows compact refrigeration equipment set up



- 01. 5UC model is designed for under counter installation with lower height (840mm)
- 02. Excellent thermal efficiency, high density polyurethane insulation with Zero ODP (Ozone Depletion Potential) and Low GWP (Global Warming Potential)
- 03. Adjustable racking system allows flexible storage
- 04. Anti-condensation door mullion heaters fitted for freezer models
- 05. Removable anti-tilt trayslides to prevent tipping
- 06. Self-closing doors minimise cool air loss and reduce energy consumption
- 07. Over 90° door opening allows easy loading and stock checking
- 08. Removable balloon type magnetic door gasket with air release points provides an excellent seal to prevent heat ingress, easy replacement and avoiding dirt traps
- 09. 20mm levelling feet at front to ensure stability on an uneven floor and 15mm castors at rear
- 10. Forced air refrigeration system ensures effective air circulation
- 11. Imported, durable and energy-efficient compressor
- 12. Condenser and evaporator with Hydrophilic aluminium fins provides high corrosion resistance properties
- 13. Accurate helium leak detection system ensures the quality of the entire refrigeration system
- 14. Automatic defrost ensures the evaporator working to its optimum performance
- 15. Automatically vaporises defrost water, drainage is not required
- 16. Designed and engineered to operate up to 43°C ambient
- 17. Environmental-friendly CFC-free refrigerant (R134a or R404a)
- 18. HACCP compliant

# Aztra

## Specification

- Accommodates 1/1 GN size
- Foodsafe 304 grade stainless steel exterior and interior
- Fitted with 1.2mm thick durable 304 grade stainless steel table top \*
- Galvanised steel exterior back and base

\* Available for 5CT(J), 10CT(J) only

## Options

1. 304 grade stainless steel exterior back / base
2. 2 drawers bank #
3. Cylindrical lock
4. Lock plate
5. Internal LED for door type
6. Additional shelving / trayslides for door type
7. 220V / 60HZ / 1PH

# Available for 5UC(J) only



## Product List

5UC(J)	5CT(J)	10CT(J)
		

# Aztra Technical Data

Model	H5UC(J)	L5UC(J)	H5CT(J)	L5CT(J)	H10CT(J)	L10CT(J)
<b>Temp Range (°C)</b>	+1 / +4	-19 / -22	+1 / +4	-19 / -22	+1 / +4	-19 / -22
<b>External Dimension (mm)</b>						
Width	650		445		865	
Depth (including 50mm rear bracket)	659				784	
Height	840				865	
<b>Internal Dimension (mm)</b>						
Width	577		375		792	
Depth	388				528	
Height	464				460	
<b>Thickness of 304 grade stainless steel (mm)</b>						
Exterior			0.7			
Interior			0.6			
Door			0.8			
<b>Opening Depth (mm)</b>						
Door type (including 50mm rear bracket)	1262		1175		1160	
Drawer type (including 50mm rear bracket)	1050				N/A	
<b>Maximum loading height of drawer (mm per drawer)</b>						
2 drawers bank	160				N/A	
<b>Capacity (cu.ft / litres)</b>	4.6 / 132		3.8 / 109		8.1 / 231	
<b>Power Supply</b>	220V / 50HZ / 1PH					
	13 amp plug					
<b>Power Input - Running (amps) *</b>						
Door type	2	4	2.15		2.23	2.5
Drawer type	2	4			N/A	
<b>Rating Power (watts) *</b>						
Door type	440	880	473		491	550
Drawer type	440	880			N/A	
<b>Compressor (HP)</b>						
Door	1/5	1/2	1/5	1/2	1/4	1/2
2 drawers bank	1/5	1/2			N/A	
<b>Heat Rejection (watts) (Evaporating at -10°C in 32°C ambient)</b>						
Door	287	1550	287	1550	485	1550
2 drawers bank	287	1550			N/A	
<b>Refrigerant</b>	R134a	R404a	R134a	R404a	R134a	R404a
<b>Standard fittings for door type</b>						
PE coated shelves			2			4
Trayslides (pair)			2			4

\* 20% increase for 60HZ power supply