

Meat Ageing Key Features

Dry ageing steak gives a fabulous end product - a steak that's tender, full of flavour and delivers a greatly enhanced dining experience









- O1. Activated carbon filter removes any organic molecules which cause odur from air circulated within the cabinet
- Himalayan salt blocks assist with moisture management, improve flavour and enhance the looks and theatre of the meat ageing display
- Removable hanging rods support the flexible arrangement in cabinet for the changeable operation flow
- O4. Excellent thermal efficiency, high density 75mm thick polyurethane insulation with Zero Ozone Depletion Potential and Low Global Warming Potential
- ∩ Anti-condensation door mullion heaters
- Adjustable and removable anti-tilt trayslides to prevent tipping
- 7. Self-closing doors minimise cool air loss and reduce energy consumption
- Over 90° door opening allows easy loading and stock checking
- Hygienic one-piece dished base with radiused corners avoids potential dirt traps
- 10. 145Hmm adjustable legs to ensure stability on an uneven floor

- 1 1. Removable balloon type magnetic door gasket with air release points provides an excellent seal to prevent heat ingress, easy replacement and avoiding dirt traps
- 12. Forced air refrigeration system with UVC anti-germicidal light keeps air flow clean
- 13. CoolSmart controller with clear temperature and humidity digital display
- 14. Imported, durable and energy-efficient compressor
- 15. Condenser and evaporator with Hydrophilic aluminium fins provides high corrosion resistance properties
- 16. Accurate helium leak detection system ensures the quality of the entire refrigeration system
- 17. Automatic defrost ensures the evaporator working to its optimum performance
- 18. Automatically vaporises defrost water, drainage is not required
- Designed and engineered to operate up to 43°C ambient
- 20. Environmental-friendly CFC-free refrigerant (R134a)
- 21. HACCP compliant



Meat Ageing

Specification

- Accommodates 2/1 GN size
- Foodsafe 304 grade stainless steel exterior and interior
- Galvanised steel exterior back and base
- Fitted with foodsafe 316 grade stainless steel drip tray for salt blocks
- Fitted with cylindrical lock for door(s)

Options

- 1. 304 grade stainless steel exterior back / base
- 2. Castors in lieu of legs
- 3. Additional shelving / trayslides
- 4. 220V / 60HZ / 1PH

Product List

BOH-MAR1



Technical Data

| Model | BOH-MAR1 |
|---|-------------------|
| Temp Range (°C) | +1 / +4 |
| Relative Humidity | 60 - 85% |
| External Dimension (mm) | |
| Width | 737 |
| Depth | 824 |
| Height | 1975 |
| Internal Dimension (mm) | |
| Width | 587 |
| Depth | 683 |
| Height | 1370 |
| Opening Depth (mm) | 1510 |
| Capacity (cu.ft / litres) | 21.6 / 613 |
| Power Supply | 220V / 50HZ / 1PH |
| | 13 amp plug |
| Power Input - Running (amps) * | 3.5 |
| Rating Power (watts) * | 770 |
| Compressor (HP) | 3/7 |
| Heat Rejection (watts) (Evaporating at -10°C in 32°C ambient) | 964 |
| Refrigerant | R134a |
| Standard fittings | |
| Stainless steel perforated shelves | 2 |
| Trayslides (pair) | 2 |
| | |

^{* 20%} increase for 60HZ power supply