

Glass Chiller Key Features

Designed for rapid chilling glasses straight from the washer



- | | |
|--|--|
| 01. Spring loaded lifting mechanism which provide easy access for users | 10. Imported, durable and energy-efficient compressor |
| 02. Fitted with double glazed Argon gas glass door to avoid condensing water | 11. Condenser and evaporator with Hydrophilic aluminium fins provides high corrosion resistance properties |
| 03. Excellent thermal efficiency, high density polyurethane insulation with Zero ODP (Ozone Depletion Potential) and Low GWP (Global Warming Potential) | 12. Accurate helium leak detection system ensures the quality of the entire refrigeration system |
| 04. Anti-condensation door mullion heaters | 13. Automatic defrost ensures the evaporator working to its optimum performance |
| 05. Self-closing doors minimise cool air loss and reduce energy consumption | 14. Designed and engineered to operate up to 43°C ambient |
| 06. Over 90° door opening allows easy loading and stock checking | 15. Environmental-friendly CFC-free refrigerant (R134a) |
| 07. Removable balloon type magnetic door gasket with air release points provides an excellent seal to prevent heat ingress, easy replacement and avoiding dirt traps | 16. HACCP compliant |
| 08. 150Hmm adjustable legs to ensure stability on an uneven floor | |
| 09. Forced air refrigeration system ensures effective air circulation | |

Note: Products are NOT designed for outdoor application, please contact Williams team for any special requirement.

Glass Chiller

Specification

- Accommodates 500 x 500mm basket
 - Foodsafe 304 grade stainless steel exterior and interior
 - Galvanised steel exterior back and base
 - Fitted with cylindrical lock
 - Fitted with 19ømm drainage for defrost water
-

Options

1. 304 grade stainless steel exterior back / base
 2. 220V / 60HZ / 1PH
-

Product List

WGC1RSL (500 x 500 basket)



WGC2RSL (500 x 500 basket)



Glass Chiller Technical Data

Model	WGC1RSL (500 x 500 basket)	WGC2RSL (500 x 500 basket)
Temp Range (°C)	+1 / +5	+1 / +5
External Dimension (mm)		
Width	900	1600
Depth	700	
Height	850	
Internal Dimension (mm)		
Width	620	620 x 2
Depth	600	
Height	575	
Thickness of 304 grade stainless steel (mm)		
Exterior	0.7	
Interior	0.6	
Opening Depth	1370	
Capacity (500 X 500mm basket)	2	4
Power Supply	220V / 50HZ / 1PH	
	13 amp plug	
Power Input - Running (amps) *	5	
Rating Power (watts) *	1100	
Compressor (HP)	1/3	
Heat Rejection (watts) (Evaporating at -10°C in 32°C ambient)	623	
Remote condensing unit with housing (Width x Depth x Height) (mm)	530 x 350 x 335	
Refrigerant Pipe Size (inch)		
Suction pipe	3/8	
Pressure pipe	1/4	
Maximum pipe length work (m)	8	
Refrigerant	R134a	

* 20% increase for 60HZ power supply

Note: all models are fitted with 19ømm drainage for defrost water